

VDM- 4010/4020

4K Over IP Matrix Encoder (TX)

4K Over IP Matrix Decoder (RX)



VDM-4010



VDM-4020



Product Features

- ▶ Supports HDCP 1.4
- ▶ Supports 4K2K@30Hz 4:2:0.
- ▶ Encoder enables HDMI 1.4 output and separates analog unbalanced 3.5mm audio output.
- ▶ With TCP/IP structure, the distance of each node can reach at least 100m.
- ▶ Decoder supports Scaler output more than 10 types of constant frequency output, realizing high compatibility with display equipment.
- ▶ Supports USB transmission for touch panels, presenters, flash drives, keyboard, mouse, and other devices.
- ▶ Decoder supports picture overlay on the receiver's displays.
- ▶ Enables remotely capture the present displays from the transmitter/receiver via TCP/IP.
- ▶ Equipped with IR two-way transmission.
- ▶ Equipped with RS232 two-way transmission.
- ▶ Equipped with 2 sets of 3.3V relay control and 1 set of 3.3V detector.



VDM-4010

VDM-4020

Hardware Specifications

HDMI (Type A)	IN x 1	OUT x 1
VGA (D-SUB)	IN x 1 OUT x 1	OUT x 1
Audio	3.5mm OUT x1	3.5mm OUT x1
	3.5mm IN x1	3.5mm IN x1
LAN	RJ45 x 1	RJ45 x 1
Fiber Uplink	SFP x 1	SFP x 1
USB Control	Type B x 1	Type A x 4
IR Receiver	LED x1	LED x 1
IR Control	3.5mm x 1	3.5mm x 1
RS-232	3P Euro terminal	3P Euro terminal
5V Output	2P Euro terminal	2P Euro terminal
3.3V Control	3P Euro terminal	3P Euro terminal
Function Key	2P Euro terminal	2P Euro terminal
	x 2	x 2
	Dip Switch x 1	
Power Input	DC 5~19V	DC 5~19V



Physical Specifications

Dimensions (WHD)	238 x 26 x 108 (mm)	238 x 26 x 108 (mm)
Weight	556.5g	556.5g
Storage Temperature	-20°C to +60°C	-20°C to +60°C
Operation Temperature	0°C- to 50°C	0°C- to 50°C



Power Supply

External Power Supply	AC 100-240V	AC 100-240V
Frequency	50-60Hz	50-60Hz
Voltage	DC 12V	DC 12V

BXB

BXB Electronics Co., Ltd.
(Headquarter in Kaohsiung, Taiwan)

A : Rm. 1, 6F., No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan (R.O.C.)

T : + 886 7 9703838

F : + 886 7 9703883

E : bxb@bxb.tw

www.bxb.tw