

Christie Terra - R

Technical specifications		Christie RXO 101 SO (166-002103-01)
Video out		<ul style="list-style-type: none"> HDMI Output format: HDMI 2.0a Content protection: HDCP 2.2 compliant Maximum resolution: 4096 x 2160, 60Hz, 8-bit 4:4:4, 10-bit 4:2:2, 10-bit and 12-bit 4:2:0 HDR, 3D and Deep Color pass through support Maximum bandwidth: 594 MHz
Audio out		<ul style="list-style-type: none"> Analog stereo: line level, 3.5mm stereo mini-jack HDMI embedded audio: multi-channel PCM, Dolby True HD, DTS-HD Master Audio
Routeable control ports		<ul style="list-style-type: none"> Serial RS-232: 9-PinD, up to 115.2K baud Wired IR in: 3.5mm stereo mini-jack Wired IR out: 3.5mm DC mini-jack USB 2.0: type-A plug Ethernet (1000BaseT) RJ45
Video processing		<ul style="list-style-type: none"> Video is uncompressed, except 4K/60 input formats including 8-bit 4:4:4, 10-bit 4:2:2, 10-bit and 12-bit 4:2:0. Ultra-lightweight 1.3-to-1 compression ratio is used for these formats which is artifact-free Color space, bit depth and frame rate conversion Video wall magnification including synchronization and bezel compensation Image compositing and multi-viewer functionality
Latency		<ul style="list-style-type: none"> Zero-frame latency mode: < 100µs, see reference guide for details
Network		<ul style="list-style-type: none"> Content transport and control: 10G Ethernet, SFP+ Optional control: 1000BaseT Ethernet, RJ45 Protocols: IP, TCP, UDP, IPv4, IGMPv2 Content encryption: AES 128-bit
Front panel LED indicators		<ul style="list-style-type: none"> Link validation for: video signal, transmit, receive, 1G Ethernet, USB, power Button 1: supply EDID to transmitters Button 2: programmable (future)
Dimensions		<ul style="list-style-type: none"> (WxHxD) 8.41 x 1.66 x 6.22" (213.5 x 42 x 158mm) case only (WxHxD) 8.41 x 1.66 x 6.50" (213.5 x 42 x 165mm) including connectors
Sound pressure		<ul style="list-style-type: none"> Less than 38dBA on a tabletop from a distance of 0.5m (typical)
Material		<ul style="list-style-type: none"> Steel, painted black
Environment	operating temperature	<ul style="list-style-type: none"> 32-104°F (0-40°C)
	storage temperature	<ul style="list-style-type: none"> -4-140°F (-20-60°C)
	operating humidity	<ul style="list-style-type: none"> 20-90% RH (non-condensing)
External power supply	input	<ul style="list-style-type: none"> 100-240 VAC @ 50-60Hz
	output	<ul style="list-style-type: none"> 12V DC, 3.0A, 36W maximum
	typical operation	<ul style="list-style-type: none"> 10W, 35 BTU
Weight		<ul style="list-style-type: none"> 2.3lbs (1.1kg) excluding power supply 2.8lbs (1.3kg) with power supply
Reliability		<ul style="list-style-type: none"> MTBF > 50,000 hours MTTR < 15 minutes
Regulatory		<ul style="list-style-type: none"> CE/FCC Class A, Directives (EC) 2011/65/EU (RoHS), 2012/19/EU (WEEE), Regulation (EC) No. 1907/2006 (REACH)
Manufacturing location		<ul style="list-style-type: none"> Designed and developed in Canada, USA and Taiwan Manufactured in Taiwan
Warranty		<ul style="list-style-type: none"> Limited two years parts and labor
UPC		<ul style="list-style-type: none"> 723466962612

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Columbia
ph: +57 (318) 447 3179

Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)
ph: +49 221 99 512-0

Germany (Moechengladbach)
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan
ph: +81 3 3599 7481

Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000

Singapore
ph: +65 6877 8737

South Korea
ph: +82 2 702 1601

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 (0) 4 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com



Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4637 Jan 18

CHRISTIE®