

FEATURES

- Single display dual channel.

- The receiver uses advanced PLL phase-locked loop and microcomputer CPU control system and is compatible with manual frequency selection and automatic infrared frequency locking.

- The receiver system adopts high performance speech companding technology to provide perfect sound quality.

- Support 6 sets of 12 frequencies being used at the same zone without interference with each other.

- Applicable to classrooms and conference rooms, etc.

SPECIFICATION

SYSTEM SPECIFICATIONS		
Frequency Range	640 - 690 MHz	
Oscillation Mode	Phase-locked loop frequency synthesis (PLL)	
Number of Channel	200	
Frequency Response	50-15KHz (±2dB)	
Working Distance	50m on open space	
Frequency Interval	250 KHz	
Carrier Wave Stability	±10PPm ≤ 10KHz	
Image Interference Ratio	>80dB	
SNR	>105dB (1KHz-A)	
Sensitivity	-105dBm (12dB S/N AD)	
THD	0.5% (ref. ±40KHz deviation. 1KHz tone)	
Muted Method	Muted and sound code locked loop	

Website: www.starviewint.com | Email: sales@starviewint.com | Tell: +65 31575338

STAR^{International}

	RECEIVER SPECIFICATIONS
Display	LCD display
Working Temperature	-10°C + 60°C (not battery operating temperature)
Case	Galvanized cold-rolled plate
Audio Output Level	Unbalanced 600Ω, load -2 dBV
Output Impedance	Unbalanced 600Ω
Unbalanced Output	TRS 6.35mm connector
Power Supply	DC 12V - 1A
Dimension (L x W x H)	420 x 180 x 41 mm
Weight	1.48 Kg (excluding antenna)

MICROPHONE SPECIFICATIONS

Frequency Range	640 - 690 MHz
Output Power	High power 30mW
Harmonic Radiation	< -55dBc
Maximum Deviation	± 70KHz
Maximum Input Sound Pressure	140dB SPL
Oscillation Mode	FM PLL frequency synthesis
Frequency Adjustment	Automatic locking and manual adjustment of receiver working channels
Battery	2 AA 1.5V batteries
Weight	0.32Kg(hand-held), 0.04Kg(lapel),(excluding battery)
Dimension	249(L) x 35(D) (hand-held), 109(L) x 64.3(W) x 21(H) (lapel)

Corporate offices

STARVIEW INTERNATIONAL PTE LTD Singapore Headquarters 60 Kaki Bukit Place #05-19 Eunos Techpark Singapore 415979

Tel: +65 3157 5338 Fax: +65 3112 8181

Worldwide offices

Vietnam

Hanoi Office R10, 33th Floor,C2 Building, D'Capitale, 119 Tran Duy Hung Street, Trung Hoa – Cau Giay, Hanoi Ho Chi Minh Office #C9-16, Block A, Sky Center Building, #10 Pho Quang Street - Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268 Hotline: 19008695 Sale Contact: 0866.207.855

Representatives

Brazil Tel: +55 11 9-8244-7630

Germany Tel: +49 172 946 69 39

France - Benelux - Africa Tel: +33 782 702 214

Southern, Eastern Europe & Middle East Operations Tel: +420 602 66 75 66



STARVIEW

For the most current specification information, please visit http://www.starviewint.com Copyright 2022 STARVIEW INTERNATIONAL PTE LTD. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. STARVIEW INTERNATIONAL PTE LTD management system is registered to ISO 9001 and ISO 45001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.