



## A POWERFUL ALL-INCLUSIVE SIGNAGE SOLUTION FOR OUTDOOR BUSINESS MESSAGING

### DESCRIPTION

Starview's Outdoor Digital Signage SSV55IP65 delivers an all-inclusive engagement solution that is completely equipped for virtually any outdoor environment. Perfect for bus stops and roadside billboards with high brightness and a built-in light sensor, your content will shine day or night. Plus, you can easily manage your signage remotely thanks to an embedded media player.



Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338



**KEY FEATURE**




**Outstanding Visibility**

At 2000 nits, this high brightness display delivers excellent legibility and visibility, even in bright sunlight. With a built-in lighting sensor, the display automatically adjusts brightness based on the ambient light to optimize visibility for day or night, while maintaining efficient operating costs for your business.

**Secured Protection with IP65 Design**

The display is sealed with IP65 design for reliable operation. It's designed to be not only waterproof but also weatherproof against the damaging effects of the sun, rain, snow, dust and wind, an essential feature for outdoor application.



**Protective Glass**

Screen surface covered with 6mm thick AR Glass, anti-ultraviolet, anti-glare, light transmittance >96%, high hardness coat film protect from sand and stones damage.

**Easy setup & Maintenance**

The embedded Media player, allows for easy content management and helps to ensure seamless content transitions and playback. All without the need for an external signage player or PC.



Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338

## OUTDOOR DIGITAL SIGNAGE SSV55IP65 SPECIFICATIONS

Panel	Screen Size (Diagonal)	55"
	Display Technology	LCD
	Aspect Ratio	16:9
	Display Resolution	1920 x 1080
	Display Area (WxH)	1209.6 x 680.4 mm
	Backlight	Direct-lit LED
	Brightness	2000 cd/m <sup>2</sup>
	Contrast Ratio	1400:1
	Display Colors	8 bit – 16.7 million
	Refresh Rate	60 Hz
	Response Time	6 ms
	Lifetime	> 60,000 hrs
	Runtime	24/7
Connectivity	HDMI, USB, Wifi/ LAN	
System	Intel core I3, RAM 8GB DDR3, 128GB SSD	
Feature	Built in light sensor, brightness adjust according to surrounding	
Power Supply	100-240V AC @ 50-60hz	
Speaker	2 x 10W	
Environment Conditions	Operating Temperature	-20°C ~ 60°C, industrial air conditioner temperature control system
	Storage Temperature	-30°C ~ 70°C
	Operating Humidity	10% ~ 85%
	Storage Humidity	5% ~ 95%
Protection	IP65, covered with explosion-proof AR Glass, light transmission >98%, includes leakage protection switch, lightning protection device and time control switch	
Structure	Material	1.5mm stainless steel SPCC
	Color	Black
Dimension (W x H x D)	1420 x 960 x 400 mm	

### Corporate offices

#### STARVIEW TECHNOLOGIES PTE LTD

**Singapore Headquarters**  
60 Kaki Bukit Place  
#05-19 Eunos Techpark  
Singapore 415979

Tel: +65 3157 5338  
Fax: +65 3112 8181

### Worldwide offices

**Vietnam**  
**Hanoi Office**  
R9, 33th Floor, C2 Building, D'Capitale,  
119 Tran Duy Hung Street,  
Trung Hoa – Cau Giay, Hanoi  
**Ho Chi Minh Office**  
#C9-16, Block A, Sky Center Building,  
#10 Pho Quang Street,  
Tan Binh District, Ho Chi Minh City  
**Danang Office**  
Add: Suite 607, Floor 6th Altara Suites  
by Ri-yaz 120 Vo Nguyen Giap, Phuoc My,  
Son Tra, Danang

Tel: (024) 66661268  
Hotline: 19008695  
Sale Contact: 0866.207.855

**Australia**  
**NGITECH PTY LTD**  
Level 40 140 Williams Street  
Melbourne VIC 3000

Tel: +61 455 225 908

### Representatives

**Brazil**  
Tel: +55 11 9-8244-7630

**Germany**  
Tel: +49 172 946 69 39

