



## Extreme-narrow bezel LCD Video Wall

The Starview ST4617 LCD Video Wall System is the ultimate LCD video wall solution for applications seeking the very best visual performance and mission-critical reliability.

ST4617 is a 46" tiled LCD video wall display with features a unique design that optimizes the extremely thin bezel LCD with 24x7 operation, minimal installation depth and simplified design, installation and service. With a tiled bezel as small as 1.7mm, ST4617 includes a built-in Daisy Chain Video Wall Controller solution, reducing total-cost-of-ownership while delivering the most reliable LCD video wall solution.

### Starview ST4617 Complete Features

- Full HD resolution displays
- Offered in 2x2, 3x3, 4x4, etc configurations
- LCD technology with WLED backlight
- Tiled bezel width of 1.7 millimeters
- Simple installation with Starview Wallmount 600x600mm VESA
- Each LCD panel built in daisy chain controller board
- Designed for 24/7 operation
- Anti-glare coating



# Built-in Daisy Chain Video Wall Controller

With each LCD panel built-in Daisy Chain Video Wall Controller to configure the displays into daisy chains as large as 2x2, 3x3, 4x4 or any array without requiring expensive external graphic cards or video processor. Implement configurations based on daisy chain through the use of DVI loop.



*Zoom in across multiple displays*

*Picture in Picture (PiP)*

## Installed for many display applications



## ST4617 LCD VIDEO WALL SYSTEM SPECIFICATIONS

Display Technology	LCD
Active Screen Diagonal	46"
Panel Dimension (WxH)	1018.08 x 572.67 mm
Total Bezel Width	1.7 mm
Panel Resolution	1920 x 1080 (16:9)
Backlight	WLED
Brightness	500 cd/m <sup>2</sup>
Contrast Ratio	4000:1
Viewing Angle	H 178°   V 178°
Display Colors	8 bit - 16.7 million
Refresh Rate	60Hz
Response Time	≤ 6 ms
Lifetime	> 60,000 hrs
MTBF	> 100,000 hrs
Power Consumption	≤ 160W Maximum; < 3W Standby
Power Supply	100-240 VAC @ 50-60Hz
Working Temperature	0°C ~ 50°C
Store Temperature	-20°C ~ 60°C
Power Supply	100-240 VAC @ 50-60Hz
Panel Weight	24kg (53lbs)
Features	<ul style="list-style-type: none"> <li>• Designed for 24/7 operation</li> <li>• Featuring a reliable power supply and cooling system</li> <li>• Anti-glare coating</li> <li>• Built in daisy chain controller board</li> </ul>

## DAISY CHAIN VIDEO WALL CONTROLLER BOARD SPECIFICATIONS

Daisy chain signal	DVI-I dual link
Video Inputs	1 x HDMI, 1 x VGA
Control	1 x RS-232 IN and 1 x RS-232 OUT
Power Input	100-240 VAC @ 50-60Hz
Control Method	IR Remote & Software Control
Main Function	Support Vertical/Horizontal Display; Support combine all screens together to show 1 image; Support PIP/Room/Zoom features.