



LCD display for performance-driven video walls

With the ultra-narrow 3.5mm combined bezel width, you get a near-seamless display that doesn't interfere with viewing ability across your video wall.

Featuring advanced panel matching, the brightness and color of each panel comes calibrated, eliminating much of the image adjustments typically required when installing video walls. The result of this barely there bezel is a seamless video wall with incredible impact, whether in a board room, control room, retail space or anywhere else you want your audience to focus on the image.

Key Features



Ultra-narrow Bezel

An exceptionally Ultra-narrow 3.5mm combined bezel enables content to be displayed as one immersive, seamless image, eliminating distortion.



Bright Non-Glare Picture Quality 24/7

An impressive 500-nit brightness and non-glare panel provides high visibility 24/7, regardless of ambient light.



View Content from Any Angle

Wide viewing angles allow viewers to get clear and accurate information, regardless of video wall layout or location.



Modern, Slim Design

The ST5535 display features an ultra-slim depth. It saves space and creates a clean, modern look for retail or other public spaces.



Accurate, Factory-Calibrated Color

Starview's multi-step factory calibration process tunes video walls to uniform brightness and color throughout multiple displays.

ST5535 ULTRA-NAROW BENZEL VIDEO WALL SPECIFICATIONS

Display Technology	LCD
Active Screen Diagonal	55"
Panel Dimension (WxH)	1213.4 x 684.2 mm
Total Bezel Width	3.5 mm
Panel Resolution	1920 x 1080 (16:9)
Backlight	Direct-lit LED
Brightness	500 cd/m ²
Contrast Ratio	1500:1
Viewing Angle	H 178° V 178°
Display Colors	8 bit - 16.7 million
Refresh Rate	60 Hz
Response Time	≤ 5 ms
Lifetime	> 60,000 hrs
MTBF	> 100,000 hrs
Power Consumption	≤ 200W Maximum; < 3W Standby
Power Supply	100-240 VAC @ 50-60Hz
Operating Temperature	0°C ~ 50°C
Store Temperature	-20°C ~ 60°C
Operating Humidity	10% ~ 85% RH
Store Humidity	5% ~ 95% RH
Panel Weight	28kg (62lbs)
Features	<ul style="list-style-type: none"> • Designed for 24/7 operation • Featuring a reliable power supply and cooling system • Anti-glare coating • Built in daisy chain controller board • Simple installation with Starview Wallmount 600x400mm VESA

DAISY CHAIN VIDEO WALL CONTROLLER BOARD SPECIFICATIONS

Daisy chain signal	HDMI
Video Inputs	1 x DVI-I Dual link, 1 x HDMI, 1 x DP, 1 x VGA
Control	1 x RS-232 IN and 2 x RS-232 OUT
Power Input	100-240 VAC @ 50-60Hz
Control Method	IR Remote & Software Control
Main Function	Support Vertical/ Horizontal Display; Support combine all screens together to show 1 image.