



Feature

- Button-type digital adjustable Volume (0dB/-3dB/-5 dB/-10 dB/-15 dB/OFF); Base(+6dB/+2 dB/0dB/-2dB-6dB); Treble(+6 dB/+2 dB/0 dB/-2dB/-6dB).
- Four conference modes: FIFO (first-in first-out mode); NORMAL (normal mode); FREE (free mode); APPLY (apply speaking).
- Function to limit the number of spokesman: adjustable speech units number: 1, 2, 4, 6; chairman unit is not restricted by it.
- Super extended limitation function; one controller can connect up to 128 units; one system can support up to 4096 units.
- "Hand in Hand" cable connected mode, easy to install and maintenance.
- Audio processing uses digital equalization module, noise reduction processing module to ensure sound clear and bright; there are two audio inputs and four audio outputs to connect peripheral devices.
- It has two output channels for original sound, which can be connected with amplifiers to amplifier the speaker voice and can be connected to cassette for recording.
- It has two recording output channels, which can connect the device to record.
- With Voting and data management function, it can be used with PC control software, other Starview conferencing systems, central control system and other equipments to achieve a modern high-tech conference.
- Working with telephone coupler, it can achieve teleconference.
- Working with video camera tracking system to achieve automatic tracking function.
- It passed the 3500V high voltage test.
- Metal shell and internal circuit have strengthened the connection with the ground to ensure the 8000V antistatic ability.
- Controller can be installed in the 19' standard rack, which is convenient for installation and maintenance.

Specifications

Model	STC-128M
Input Power Supply	~90 – 132V/180-264V 50/60Hz by Switch
Mic Capacity	≤4096
Channel Numbers	1 CH
Frequency Response	30 ~ 20KHz
Snr	>72 dB(A)
Channel Crosstalk	>80 db
Thd	<0.05%
Audio Input	LINE IN: 775mV unbalanced
	MIC IN: 50mV unbalanced
Audio Output	LINE OUT: 1V unbalanced
	REC OUT: 200mV unbalanced
Output Load	>1K
Serial Port	Connect to PC and video tracking controller
Static Power Consumption	10W
Output Comsumption	340W
Connect Way	Special cables (8 cores)
Connector Reliability	Reliability
Standards	IEC60914
Operation Temp	~10°C~+60°C
Operation Humidity	20%~80% related humidity, no condensing
Color	Black
Weight	3KG
Dimension	484 x 305 x 88 mm
Installation Method	19 inch standard rack