



# STARVIEW SV-CSPM SERIES

LCD MONITOR

Copyright © 2022 Starview Technologies Private Limited. All rights reserved.

Singapore Headquarters: 60 Kaki Bukit Place, #05-19 Eunos Techpark, Singapore 415979

Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338




## DESCRIPTION

*The Starview SV-CSPM Series with highly durable design that can operate continuously for 24 hours even in harsh environments; power saving design and thin housing design that contributes to beautiful screen power saving with full HD panel & slim bezel. UHD resolution guarantee eye-pleasing image quality for ergonomic viewing and versatile digital connectivity optimized to the needs of corporate and signage applications. It is widely used in modern education teaching, interactive business commerce presentations, meetings, medicine, army etc...*

## FEATURES


- LCD technology with Edge LED backlight, 3840 x 2160 resolution, 500 nits.
- Designed for 24/7 operation.
- 10 points infrared simultaneously touch (optional)
- Default wallmount bracket.
- Support: Vertical/ horizontal rotation, Smart Energy Saving features.
- Screen high-definition display, accurate and clear colors, rich and lifelike content, giving people a sense of being in it.

Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338



### Fast Response

With a fast 8ms response time, blur, ghosting and distortion will be eliminated, giving way to a perfect dynamic picture.



### Wide Viewing Angle

Expanded vision with 178 degrees viewing angle, no deformed pictures and no color distortion, perfect viewing.



### Material

Our full metal shielding structure will prevent any exterior electromagnetic interference.



### High Quality Audio

Our units are equipped with high quality digital audio outputs.



### High Definition Displays

Only professional/ commercial grade A+ are used for our products. High brightness and contrast ratios are the key in delivering great visible advertising.



### Intelligent temperature control system

Our intelligent temperature control system will regulate and protect the equipment. Keeping the unit performance at peak level.



### Operating System

Support: Android 8.0

## APPLICATIONS

The Starview SV-CSPM Series LCD Monitor can be use in a variety of settings, including classrooms at all levels of education, in corporate board rooms and work groups, in training rooms for professional sports coaching, in broadcasting studios and others.



Business Meeting



Video Conference



Broadcasting Studio



Lobby

## SPECIFICATION

### STARVIEW SV-CSPM SERIES LCD MONITOR SPECIFICATIONS

Model	SV-CSPM554K	SV-CSPM654K	SV-CSPM754K	SV-CSPM864K	SV-CSPM984K
Display Technology	IPS LCD				
Active Screen Diagonal	55"	65"	75"	86"	98"

Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338

Active Display Area (W x H, mm)	1208.6 x 677.9	1428.2 x 803.2	1646 x 925.5	1892.2 x 1064.2	2158.8 x 1214.3
Panel Resolution	UHD 3840 x 2160 (16:9)				
Display Colors	10 bit, 1.07 billion colors				
Refresh Rate	60Hz				
Brightness	500cd/m <sup>2</sup> , can adjust brightness				
Contrast Ratio	1200 : 1				
Lifetime	30,000 - 50,000 hours				
Viewing Angle	178° H/V				
Backlight	Edge LED				
Runtime	24/7				
Response Time	8 ms				
Touch Screen	Optional				
Input	1x 4K HDMI input, 1x RF, 1x VGA, 1x RJ45, 1x 4K DP option				
Speaker	2 x 10W				
O/S	Support Android 8.0				
Material	Quality SPCC & Aluminium frame				
Frame Color	Siver gray				
Surface Treatment	Haze 10%				
Power Supply	110 ~ 240V AC, 50/60Hz				
Power Consumption	120W	220W	270W	330W	380W
Operation Temperature	0°C ~ 40°C				
Operation Humidity	10% ~ 80%				
Dimension (W x H x D, mm)	1257.7 x 745.2 x 103.5 mm	1483.6 x 898.6 x 119.9 mm	1705.8 x 1013.5 x 120.1 mm	1952 x 1152.5 x 120.1 mm	2215.8 x 1306.6 x 128.65 mm
VESA Mount (mm)	400 x 400	500 x 400	600 x 400	800 x 400	1000 x 400
Weight	23.5Kg	37Kg	54Kg	66Kg	75Kg

## Corporate offices

**STARVIEW TECHNOLOGIES PTE LTD**  
Singapore Headquarters  
60 Kaki Bukit Place  
#05-19 Eunos Techpark  
Singapore 415979

Tel: +65 3157 5338  
Fax: +65 3112 8181

## Worldwide offices

**Vietnam**  
**Hanoi Office**  
R10, 33th Floor, C2 Building, D'Capitale,  
119 Tran Duy Hung Street,  
Trung Hoa – Cau Giay, Hanoi  
**Ho Chi Minh Office**  
#C9-16, Block A, Sky Center Building,  
#10 Pho Quang Street - Tan Binh District,  
Ho Chi Minh City

Tel: (024) 66661268  
Hotline: 19008695  
Sale Contact: 0866.207.855

## Representatives

**Brazil**  
Tel: +55 11 9-8244-7630

**Germany**  
Tel: +49 172 946 69 39

**France - Benelux - Africa**  
Tel: +33 782 702 214

**Southern, Eastern Europe  
& Middle East Operations**  
Tel: +420 602 66 75 66

