



DESCRIPTION

The CS-30P is a ceiling speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers. The built-in 5" + 1.5" coaxial speaker driver is designed of wide frequency response 100-18 kHz, and its various power output from 3.75W, 7.5W, 15W & 30W could meet different room size applications. The power taps is convenient to switch the input from 100V to 70V or 8Ω, thus this speaker support both high impedance input and low impedance input use. The metal grille, ABS baffle and ABS back cover are painted in attractive white color. Its flush mount type makes the easy and secure installation. It is ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

KEY FEATURES

- Built-in 100v/70v transformer
- In-ceiling type loudspeaker
- 5" + 1.5" coaxial speaker unit
- Power output 3.75W, 7.5W, 15W & 30W @100V
- Built-in crossover for hi-fi use
- Line input: 100V, 70V or 8Ω
- Metal grille, ABS baffle & ABS back cover
- Paint in white color
- Secure flush mount installation

Website: www.starviewtech.asia or www.starviewtech.net | Email: sales@starviewint.com | Tell: +65 31575338

SPECIFICATION

STARVIEW CS-30P SPECIFICATIONS

Model	CS-30P
Speaker Driver	5
Cutout Size	210 mm
Dimensions	240 x 155 mm
Weight	2.1Kg
Mounting	Flush - mount dog ears
Power Taps @100V	3.75W, 7.5W, 15W, 30W
Power Taps @70V	1.9W, 3.75W, 7.5W, 15W, 30W
Input	70V/100V/ 8Ω
Transformer Impedance	Black: Com Red: 2.7KΩ/ 1.3KΩ/ 670Ω/ 330Ω/ 165Ω
SPL(1W/1M)	89dB
Max. SPL (Rated W/1M)	106dB
Frequency Response (-10dB)	100Hz - 18KHz
Finish	Baffle: ABS, White Grille: Steel, White
Operating Temperature	0°C ~ 40°C
Operating Humidity	10% ~ 90%RH (non-condensing)
Storage Temperature	0°C ~ 40°C
Storage Humidity	10% ~ 90%RH (non-condensing)