

# EL-LW906U

LASER PROJECTOR



## OVERVIEW

The Starview EL-LW906U takes 3LCD technology to the next level in resolution and cost effective performance by offering native WUXGA (1920×1200) resolution and Starview's proven image quality.

## KEY FEATURES

### Reliability you can trust

Get extra peace of mind with our industry-leading warranty and virtually maintenance-free operation that works for you 24/7.

› **Dynamic contrast for lifelike imagery:** Dive into a world of depth and detail with a dynamic contrast ratio of 3,000,000:1.

› **Cutting edge, advanced electronics:** Liquid Crystal Display 3x0.76"WUXGA and optical design give you improved color, contrast, and a more efficient cooling system design.

› **Wide range of lens options:** With many interchangeable lenses, including ultra-short throw, you can find the lens that works best for your project.

› **Reliable laser light source:** 20,000 hours in Standard mode and 30,000 hours in Eco Mode.



**Technical specifications****EL-LW906U**

<b>Image</b>	Projector Type	Liquid Crystal Display 3x0.76"WUXGA
	Native Resolution	WUXGA (1920x1200) 4K enhancement
	Brightness	20,000 Lumens
	Uniformity	90%
	Contrast	3.000.000:1
<b>Light Source</b>	Aspect Ratio	16:10 Native / 4:3 Compatible
	Type	Laser Technology
<b>Projector lens</b>	Life	Standard: 20,000 hours. Eco Mode: 30,000 hours
	Manual	Standard: 1.46-2.95:1; Ultra Long: 4.59-7.02:1
<b>Keystone Correction</b>	Motorized	Short: 0.6-0.75:1; Short: 0.79-1.11:1; Standard: 1.3-3.02:1; Long: 2.99-5.93; Ultra Short: 0.32:1
	H	±50°
<b>Projection Method</b>	V	±30°
		Ceiling, Front, Rear
<b>Input</b>		DVI-D x1
		HDMI 1.4 (SupportHDCP) x1
		15-pin Mini-Dsub x1
		HDBaseT x1
		Wired Remote x1 3.5mm
		RJ45 x1 (LAN Control)
		RS232 (D-sub 9pin) x1
		USB-A x1 (5V/1.5A) USB-B x1
<b>Output</b>		15-pin Mini-Dsub x1
		HDMI 1.4 (Support HDCP3) OUT x1
		3D-Sync x1
<b>Power Input (Voltage &amp; Frequency)</b>		100-240V AC±10%, 50/60Hz
<b>Power Consumption</b>		Normal: 1050W, ECO: 850W
<b>Case Material</b>		Molded Plastic
<b>Standby Power Consumption</b>		<0.5W
<b>Dimension D x W x H</b>		600 x 218 x 503mm
<b>Net Weight</b>		28.5 kg
<b>Noise</b>		Normal: 35dB, ECO: 33dB
<b>Operating Environment</b>	High Altitude	0m-2500m (>1500m Using High Altitude Mode)
	Temperature	5°C - 40°C
	Humidity	10% - 85%RH non-condensing
<b>Accessories</b>		AAA Battery x2, Remote Control x1, Power Cablex1, VGACable x1, Lens cover

For technical or sales support, please visit:

[www.starviewint.asia](http://www.starviewint.asia)

*Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.*

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact [info@starviewint.asia](mailto:info@starviewint.asia)

Copyright © 2025 STARVIEW ASIA. All rights reserved.  
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia