

# M-500S

PROFESSIONAL SPEAKER



## DESCRIPTION

It works with the professional amplifier and audio processors. It can be used as a monitor speaker in large conference halls and multi-function halls, etc.

## FEATURE

- Use a mid-woofer and an annular polyethylene diaphragm compressed tweeter.
- 15mm plywood housing, light weight, wear-resistant spray paint treatment, external hard hexagonal iron mesh, and dust-proof cotton inside.
- The frequency divider in precise design optimizes the vocal MF performance.
- The cabinet has a polygonal structure, and the monitoring angle can be adjusted according to different venues.

## Technical specifications

### M-500S

Impedance	8Ω
Frequency response	45Hz-20KHz
Rated power	500W
Peak power	2000W
Sensitivity	100dB/W/M
Maximum SPL (rated/peak)	127dB/133dB
Coverage angle	(H)90° (V)70°
Tweeter	1.7" compressed tweeter × 1
Woofer	15" woofer × 1
Size (H×W×D)	395×690×465mm
Weight	26.5Kg

---

For technical or sales support, please visit:

**[www.starviewint.asia](http://www.starviewint.asia)**

*Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.*

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact [info@starviewint.asia](mailto:info@starviewint.asia)

Copyright © 2025 STARVIEW ASIA. All rights reserved.  
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia

