

PA2-2000

PROFESSIONAL AMPLIFIER



FEATURE

- Dual-channel high-power professional digital power amplifier;
- The power amplifier has DC, short circuit, overload and overheat protection;
- Adopt variable oscillation modulation technology, multiple feedback control technology and innovative output power control technology to achieve more than 95% ultra-high efficiency and excellent stability;
- Input sensitivity (rated output power@1KHz) optional: 42dB, 39dB, 36dB, 33dB;

DESCRIPTION

This series of products is the latest generation of high-power professional digital power amplifiers, featuring high efficiency, stability and excellent sound quality. It is specially designed for large-scale sound reinforcement, performances in multi-function halls, etc.

- With signal, power, temperature limit function;
- Three modes of MONO/STEREO/BRIDGE can be switched;
- With temperature-controlled fan, which will run when booting, and will accelerate as the temperature increases. The full speed is about 60 degrees;
- The panel has signal indicator (green), clipping indicator (orange), protection indicator (red), and power indicator (blue);
- Regular load is 8 Euros, 4 Euros, and minimum 2 Euros.

Technical specifications**PA2-2000**

Output power (1KHz/THD≤1%)	Stereo 8Ω: 2x2000W;Stereo 4Ω: 2x3400W;Stereo 2Ω: 2x4760W;Bridge 16Ω: 1x4000W; Bridge 8Ω: 1x6800W;Bridge 4Ω: 1x9520W;
Connecting socket	XLR interface
Input Sensitivity (Rated Output Power, @1KHz)	42dB, 39dB, 36dB, 33dB, optional
Input impedance	10KΩ unbalanced, 20KΩ balanced
Frequency response (Under @1W power)	20-20KHz/±1dB
THD+N (Under @1/8 power)	≤0.01%
SNR (A-weighted)	≥106dB
Damping Factor (@ 1kHz)	≥200@ 8 ohms
Crosstalk (@1kHz)	≥85dB
Protection method	Overvoltage protection, undervoltage protection, overcurrent protection, DC protection, short circuit protection
Indicator light	Power, Protection, Signal, Distortion
Cooling method	Fan cooling
Power supply	~ 220 50Hz
Overall power consumption	1700W
Dimensions (L x W x H)	484x353x44mm
Weight	8.1kg

Notes: Output power: according to CEA-2006-B/CEA-490-A standard using 20ms pulse 1kHz sine wave measured under 1% total harmonic distortion.
Overall power consumption: according to GB4943.1-2022 test method: measured under 1kHz sine wave rated load 1/8 power conditions.

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia