

SA-W63

MICROPHONE



AUDIO CHARACTERISTICS

- Microphone frequency response: 100Hz-20KHz.
- Microphone pickup range: ≥ 5 meters.
- Microphone pickup angle: 360 degrees.
- Microphone quantity: 1.

INTERFACE CHARACTERISTICS

- Microphone interface: RJ9 interface $\times 1$.

ELECTRICAL CHARACTERISTICS

- Power supply: main microphone power supply.

FEATURES

- Adopt an integrated design and simple structure, built-in 1 digital microphone, 360° omnidirectional pickup, and the maximum pickup distance reaches 5 meters.
- One-key mute switch with clear LED status indicator.

VOICE CHARACTERISTICS

- Full duplex echo cancellation depth: ≥ 65 dB.
- Full duplex echo cancellation time: 500ms.
- Two-way noise compression: ≥ 18 dB.
- Line echo cancellation depth: ≥ 25 dB.
- Line echo cancellation time: 32ms.

WORKING ENVIRONMENT

- Reverberation time: <0.5 S.
- Noise level: <-48 dBA.

PHYSICAL CHARACTERISTICS

- Housing: Black.
- Working temperature: 0°C~50°C.
- Working humidity: 20% -85%.
- Dimension: 10.0 \times 4.0cm.
- Weight: 1kg.

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia

