

## STC-128M

### DIGITAL CONFERENCE MANAGEMENT UNIT

#### FEATURE

- Adjustable Volume (0dB/-3dB/-5 dB/-10 dB/-15 dB/OFF ); Bass(+6dB/+2 dB/0dB/-2dB-6dB); Treble(+6 dB/+2 dB/0 dB/-2dB/-6dB).
- Four conference modes: FIFO (first-in first-out mode), NORMAL (normal mode), FREE (free mode), APPLY (apply to speak).
- Support limiting the number of spokesmen: the number of speaking units can be set to 1, 2, 4 and 6; the chairman unit is not limited.
- Support super extension function: one controller can connect 128 units, and up to 4096 units can be connected through extension.
- Hand in hand cable connection mode, convenient for installation and maintenance.
- Adopt digital equalization module and noise reduction module for audio processing, ensure clear and bright sound; designed with two audio inputs and four audio outputs for connecting peripheral devices.
- Equipped with 2 original sound output channels, connected to PA amplifier for sound amplification, and connected to a deck for recording.
- Equipped with 2 recording output channels, connected to equipment for recording.



- Support voting and data management function, used with PC control software, other Starview conference systems, central control system and other devices to achieve the modern high-tech conference.
- Used with telephone coupler for achieve teleconference.
- Used with video camera tracking system for automatic tracking function.
- It has passed the 3500V high voltage test.
- Metal housing and internal circuit are well connected to the ground wire to ensure the 8000V anti-static capability.
- The controller can be installed in the 19-inch standard rack, convenient for installation and maintenance.

**Technical specifications**      **STC-128M**

Input power	~90-132V/180-264V 50/60Hz by switch
Microphone qty	≤4096
Channel number	1CH
Frequency response	30 ~ 20KHz
SNR	>72dB(A)
Crosstalk	>80 dB
THD	<0.05%
Audio input	LINE IN: 775mV unbalanced MIC IN : 50mV unbalanced
Audio output	LINE OUT : 1V unbalanced REC OUT: 200mV unbalanced
Output load	>1KΩ
Serial port	Connect to PC and camera tracking controller
Static power consumption	10W
Output power consumption	340W
Connection	Special cables (8 pins)
Connector	Reliable
Standard	IEC60914*
Working temperature	-10°C~+60°C
Working humidity	20%~80% related humidity, no condensation
Storage temperature	-10°C~+60°C
Storage humidity	20%~80% related humidity, no condensation
Color	Black
Weight	3Kg
Dimension	484 ×305× 88mm
Installation method	19-inch standard rack

\* The listed certifications are issued for markets in different regions. For the current status of the listed certifications in your region, please contact an authorized Starview representative.

For technical or sales support, please visit:

**[www.starviewint.asia](http://www.starviewint.asia)**

*Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.*

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact [info@starviewint.asia](mailto:info@starviewint.asia)

Copyright © 2025 STARVIEW ASIA. All rights reserved.  
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia