STARVIEW ASIA
TECH FOR A BETTER WORLD

STC-4096E

DIGITAL CONFERENCE SYSTEM EXTENSION CONTROLLER

FEATURE

- Use together with the Standard Digital Conference System Controller to expand system capacity by connecting more units.
- Each Extension Controller can connect 128 units after connecting to system.
- Can cascade up to 32 pieces Extension Controller.
- It passed the high voltage (3500V) test when leaving factory to meet safety standard.
- Metal shell and internal circuit have strengthened the connection with the ground to ensure the 8000V antistatic ability.
- 2U metal case can be mounted in standard 19-inch rack, easy to place and maintenance.
- Built-in universal power supply

Technical specifications	**STC-4096E**
Power Supply	~90-132V/180-264V 50/60Hz by switch
Static Consumption	10W
Output Power	340W
Audio Output	Level 2Vp-p Impedance:100Ω Unbalanced
Frequency Response	60-16KHz
SNR (S/N)	> 75dB
THD	< 0.5%
Over Carrier Distortion	<1%
Crosstalk Attenuation (1KHz)	>50dB
Interface	8-pin plug ×5 / three-core AC main power socket
Color	Black
Weight	2Kg
Dimension (mm)	484(L)×305(W)×88(H)

STARVIEW ASIA
TECH FOR A BETTER WORLD

For technical or sales support, please visit:
www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia