

STM-DS18, STM-DS18A CONFERENCE MICROPHONES

FEATURE

- It adopts a 4.3-inch IPS full-color touch screen with a simple interface.
- The microphone adopts a short microphone rod and a high-sensitivity microphone core to support long-distance sound pickup.
- Uncompressed audio transmission technology. The sampling rate is up to 48K, and it can provide perfect sound quality with a bandwidth of 80Hz-16KHz.
- It adopts 100M network transmission. And the network connection adopts network cable hand in hand, which is convenient for wiring.
- Communication adopts standard TCP/IP protocol, and each unit can support ping packet function.
- Simultaneous interpretation supports 63+1 channels, and the unit has a dual-channel listening function, which can listen to different interpreter channels at the same time.
- With two 3.5mm headphone jacks, support listen to the sound of any one of 63+1 channels or connecting an external microphone.
- The chairman unit has the priority right to turn off the speaking of the delegate unit.
- Each unit has a built-in independent web server, which supports four language switching, adjustment of microphone ID number, microphone sensitivity, microphone EQ and other parameters.
- It has the function of speech timing and timed speech, and the delegate unit can apply for speaking.
- Internal feedback suppression function, voice control function, adjustable voice control sensitivity.



- With a 5-band EQ adjustment function. Different sound effects can be adjusted according to the voice characteristics of the speaker until the perfect effect is achieved.
- Support (disk) clock display function. It can display the time. Synchronize server time.
- Support the conference logistics service function. The microphone unit can send service of tea, paper pen, manual services and other requirements to the conference controller.
- Support voting function. There are multiple voting mode options, and the content of the options can be customized and sent to the unit for display.
- Support sign-in function. You can also disable and control the unit check-in, and other functions through the PC software.
- Support firmware upgrade function on the web page.
- Support the IP address sniffing function, the ID number, IP address and MAC address of unknown units can be found by PC software

Technical specifications **STM-DS18, STM-DS18A**

Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Microphone input impedance	1K Ω
Sensitivity	-40 \pm 1dB (0dB=1V/Pa, at 1KHz)
Maximum SPL	120dB(THD<3%)
SNR	>80dB(A)
Dynamic range	>70dB
THD	<0.3%
Maximum power consumption	3.0W
Power supply	Conference server power supply
Color	Oxidized fine sand black
Dimension (L x W x H)	154.9 \times 99 \times 60.5mm (excluding the length of the microphone pole)
Microphone pole	240mm integrated square short microphone rod (light black)
Installation method	Desktop
Weight	1.01kg

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia