STARVIEW ASIA
TECH FOR A BETTER WORLD

STM-T18, STM-T18A

CONFERENCE MICROPHONES

FEATURE

- Digital transmission link, connected to the cascade port of the conference controller for power supply through a network cable, uncompressed audio transmission technology, 48K sampling rate, 80Hz-16kHz bandwidth, perfect sound quality.
- Physical buttons to ensure reliable and stable triggering.
- Support microphone control via PC software, support voice control function.
- With 1 3.5mm headset interface can be used for recording and connecting headphones.
- The chairman unit has the priority to turn off the delegate unit that is speaking.
- With TCP/IP protocol suite, it supports ICMP, HTTP, UDP, TCP, IGMP and other protocols.
- Support PING package function.
- Designed with an independent web control page, it can adjust parameters such as microphone ID and microphone sensitivity.
- Support internal voice control function, and the voice control sensitivity is adjustable.

- Support the sign-in function, and support functions such as prohibiting unit sign-in and controlling unit sign-in through the PC software.
- Support web page firmware upgrade function.
- Support IP address sniffing function; the ID number, IP address, MAC address and other parameters of unknown units can be found through PC tools.

STARVIEW ASIA
TECH FOR A BETTER WORLD

Technical specifications	STM-T18, STM-T18A
Microphone type	Electret condenser microphone
Microphone directivity	Cardioid
Frequency response	80Hz~16KHz
Input impedance	1KΩ
Sensitivity	-40±1dB (0dB=1V/Pa, at 1KHz)
Maximum SPL	120dB(THD<3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Maximum power consumption	2.5W
Power supply	Powered by the conference controller
Color	Gray
Sign-in function	Button sign in
Installation method	Desktop installation
Dimension (L×W×H)	100.9×130×54.3mm (excluding the mic pole)
Mic pole length	240mm integrated square short microphone rod (light black)
Weight	1.15Kg

For technical or sales support, please visit:
www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia