

US2-TR592

WIRELESS MICROPHONE



DESCRIPTION

It is a digital wireless microphone system with a new solution architecture. The system adopts unique digital U-band transmission technology and pi/4-DQPSK modulation mode. It is characterized by low bit error rate, stable transmission and strong anti-interference ability. In addition, it adopts ID code pilot technology to prevent co-frequency crosstalk, and adopts frequency sweep to avoid interference, etc.

FEATURE

- Based on the digital U-band transmission technology, pi/4-DQPSK modulation mode, using domestic main control chip, the transmission distance is 80 meters; it has reverberation, equalization, intelligent mute, audio encryption, and power adjustment functions.
- It has 1 receiving controller and 2 head-mounted waist bags; the frequency range is 470MHz-510MHz, 540MHz-590MHz, 640MHz-690MHz, and 807MHz-830MHz.
- It uses a unique encryption method for audio transmission to ensure the security of conference content.
- It has multi-band equalization adjustment function, 2197 types of equalization adjustment, microphone equalizer adjustment function, with three adjustment gears of high, medium and bass, and each effect supports 13 gears of adjustment.
- It has multi-gear reverberation adjustment function, 15625 reverberation effects, effect proportion, reverberation delay, and reverberation amplitude adjustment, and each of the three sound effects has 25 gears of adjustment.
- The front panel of the receiver has 2 TFT-LCD display screens, 2 encoding knobs, 2 frequency scanning physical buttons, 2 infrared frequency binding physical buttons, 1 power switch button, and 1 two-in-one indicator light (infrared transmitting tube + frequency binding indicator light); the rear panel has 1 LINE-OUT interface, 2 XLR-OUT interfaces, 2 BNC interfaces, and 1 DC interface. The transmitter has 1 display screen, 4 physical buttons (including 1 mute button, 1 volume reduction button, 1 volume increase button, 1 power switch key), 1 power status indicator light, and 1 mute indicator light.
- The receiver has 2 2.2-inch TFT-LCD display screens;
- The transmitter has a 0.96-inch OLED display screen, which can display frequency information, audio encryption status, power gear, mute status, and power grid information.
- It has two balanced outputs and one unbalanced mixed output.

FEATURE (CONT.)

- It has a one-button mute function and is very practical.
- The receiver panel is made with exquisite craftsmanship and is beautiful.
- With ID code anti-crosstalk function, it uses a 32-bit unique ID code for receiving and transmitting pairing. The sending and receiving ID codes must be the same to pair, which can effectively prevent signals of the same frequency from interfering with each other.
- One-key frequency scanning to avoid interference; one-key infrared frequency pairing, simple operation.
- With long battery life, the transmitter can be used continuously for 10 hours.
- The transmitter has a volume adjustment key to adjust the volume.
- The transmission power is adjustable in 7 levels, and the transmission power can be adjusted as needed.

Technical specifications

US2-TR592

System parameters	Frequency range	470MHz-510MHz, 540MHz-590MHz, 640MHz-690MHz, 807MHz-830MHz
	Modulation mode	pi/4-DQPSK
	Frequency response	20Hz~20kHz (± 3 dB)
	SNR	≥ 105 dB (XLR)
	THD+N	$< 0.1\%$
	Working distance	About 80m
Receiver	Antenna interface	BNC/50 Ω
	Receive sensitivity	< -95 dBm
	Maximum output	Balanced output 500mV, unbalanced output 1000mV
	Power supply	DC 12V/1A
	Working current	≤ 320 mA
	Dimension (L x W x H)	482.6x212x44mm
	Weight	2.225kg
Transmitter	Mic type	Condenser Microphone (Dual Headset Microphone)
	Output power	≥ 10 dBm
	Working current	≤ 200 mA
	Battery capacity	2x1.5V(AA)
	Battery life	> 10 H
	Dimension	86mm x 65.3 x 23.8mm (excluding mic cartridge)
	Weight	185g (including battery)

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia