

K-HD Single Side Series

Digital Signage Kiosk









DESCRIPTION

Digital Signage Kiosk K-HD Single Side Series

delivers advertising and information in any type of indoor facility, featuring a sophisticated design and 24/7 flexible operation. Boasting an aluminum hairline finish and robust glass surface, it can reliably withstand external shocks while also blending in with its surroundings.



FEATURE

	<p>Easy upgradable options available: Android, Windows and network.</p>		<p>With a fast 5ms response time, blur, ghosting and distortion will be eliminated, giving way to a perfect dynamic picture.</p>
	<p>By using the visual extension technology (S-PVA) it will give an easy 178 degrees viewing angle. No deformed pictures and no color distortion, perfect viewing.</p>		<p>Only professional/ commercial grade A+ are used for our products. High brightness and contrast ratios are the key in delivering great visible advertising.</p>
	<p>Our intelligent temperature control system will regulate and protect the equipment. Keeping the unit performance at peak level.</p>		<p>Our units are equipped with high quality digital audio outputs</p>
	<p>Equipped with 3D reduction technology.</p>		<p>Our full metal shielding structure will prevent any exterior electromagnetic interference</p>

Technical specifications

K-HD Single Side Series

Model		K431-HD	K551-HD	K651-HD	K751-HD	K861-HD
LCD panel	Screen Size	43"	55"	65"	75"	86"
	Resolution	1920x1080 (16:9)				
	Display Colors	8 bit, 16.7M colors				
	Refresh Rate	60Hz				
	Brightness	400 nits (cd/m ²)				
	Contrast Ratio	4000:1				
	Lifetime	60,000 hours				
	Viewing Angle	178° H/V				
	Response Time	5ms				
	Backlight	Direct-lit LED				
	Runtime	24/7				
Touch Screen (Optional)	Touch Screen Type	Capacitive				
	Multi Touch	10 points				
	Writing Style	Responds to finger, gloved hand or pointer				
Environment	Operating Temperature	-5°C ~ 60°C				
	Operating Humidity	10% ~ 80%				
Camera	20MP Camera built in (Optional)					
OS	Android 4 core RK3288 or Windows (Optional)					
3G/4G	Optional					
Structure	Material	Aluminum profile				
	Glass	Tempered glass				
Power	Supply	110 ~ 240V AC, 50/60Hz				
	Consumption	100W Max, < 3W Standby				
Connectivity	Lan, Wifi					

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia