

# SA-LF SERIES

INDOOR LED VIDEO WALL



## FEATURES

- Perfect to split joint without gap, it can be jointed as various of sizes or shapes.
- 160° Ultra-Wide Visual Angle, to view without blind angle and color cast, to enjoy a visual feast.
- Anti-Blue Light, Anti-Visual Fatigue
- High grayscale and refreshing, the picture is stable by dynamic display, no corrugated
- Front maintenance and installation, no need maintenance space, convenient and fast, reinforcing cover, to make it be flat.



- It can realize splicing of various sizes such as 640x480mm, 640x640mm, 960x480mm, 320x640mm.



## Technical specifications

## SA-LF SERIES

Model	SA-LF-P1.2	SA-LF-P1.5	SA-LF-P1.6	SA-LF-P1.8	SA-LF-P2	SA-LF-P2.5
Pixel Pitch (mm)	1.25	1.538	1.667	1.86	2	2.5
LED Type	SMD, RGB 3in1					
Pixel Density (pixel/m <sup>2</sup> )	640,000	422,500	358,801	288,369	250,000	160,000
Module Size (W x H)	320 x 160 mm					
Module Resolution (W x H)	256 x 128	208 x 104	191 x 95	172 x 86	160 x 80	128 x 64
Cabinet Size (W x H) (Customize)	640x480mm/640x640mm/960x480mm					
Cabinet Weight	5.5kg (640x480mm)					
Brightness	500cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>	600cd/m <sup>2</sup>
Viewing Angle (H/V)	160° /160°					
The Optimal Visual Distance	1m	1.5m	1.6m	1.86m	2m	2.5m
Grayscale	It is available within 65,536 grade					
Display Color	14 Bit					
Frame Rate	50/60 Hz					
Refresh Rate	3840 Hz					
Runtime	24/7					
Lifetime	100,000 hours					
Heat Output Per Sqm	614 BTU/hr typical, 1911 BTU/hr maximum					
The Max Power Consumption	560W/m <sup>2</sup>					
The Average Power Consumption	180W/m <sup>2</sup>					
Protection Grade	IP20					
Power Supply	100-240 VAC @50/60Hz					
Working Temperature/Humidity (°C/RH)	-10~50°C/10%~95% (non-condensing)					
Storage Temperature/Humidity (°C/RH)	-20~60°C/10%~95% (non-condensing)					

For technical or sales support, please visit:

[www.starviewint.asia](http://www.starviewint.asia)

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact [info@starviewint.asia](mailto:info@starviewint.asia)

Copyright © 2025 STARVIEW ASIA. All rights reserved.  
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia