



SA-SFPP-10GLD

10.3125Gbps Long Wavelength SFP+ Optical Transceiver

DESCRIPTION

SA-SFPP-10GLD is specifically designed for the high performance integrated duplex data transmission over single mode optical fiber. This transceiver module is compliant with the Small Form-factor Pluggable Plus (SFP+) Multisource Agreement (SFF-8431 Rev4.1). This transceiver type is specifically optimized for transport of serial data at up to 10.3125 Gbps, with link characteristics complied with 10-Gigabit Ethernet 10GBASE-LR base IEEE 802.3ae and 10G Fibre Channel 1200-SM-LL-L. 5

APPLICATIONS

- 10GBASE-LR/LW 10G Ethernet
- 1200-SM-LL-L 10G Fibre Channel

FEATURES

- Duplex LC Connector
- Support hot-pluggable
- Metal with lower EMI
- Excellent ESD protection
- DFB Transmitter and PIN Receiver
- Typical Center Wavelength: 1310nm
- Max link length up to 10Km on SMF
- RoHS Compliant and Lead-Free
- Digital diagnostic compatible with SFF-8472
- Case Operation Temperature: -5°C~+70°C
- Single 3.3V power supply and Low power dissipation <1.0W

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Maximum Supply Voltage	Vcc3	-0.5	-	4.0	V	
Storage Temperature	TS	-40	-	85	°C	
Operating Humidity	-	5	-	95	%	
Maximum Supply Voltage	Vcc3	-0.5	-	4.0	V	

RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage	V _{cc}	3.13	3.30	3.47	V	
Power Supply Current	I _{cc}	-	-	300	mA	
Case Operating Temperature	T _{op}	-5	-	70	°C	
Data Rate	-	-	10.3125	-	Gb/s	
9/125um G652 SMF	L _{max}	-	-	10	Km	
Baud Rate Tolerance		-100		+100	ppm	

PERFORMANCE SPECIFICATIONS - TRANSMITTER

(-5°C<T_c<+70°C; +2.97V<V_{cc}<+3.63V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes	
Input Differential Impedance	Z _{in}	90	100	110	Ω		
Tx_Fault	Normal Operation	VOL	-0.3	-	0.4	V	
	Transmitter Fault	VOH	2.4	-	V _{cc}	V	
TX_Disable (Note 1)	Disable	VIH	2.0	-	V _{cc} +0.3	V	
	Enable	VIL	-0.3	-	0.8	V	
Average Launch Optical Power	P _{out}	-8.2	-	0.5	dBm		
Optical modulation amplitude	P(OMA)	-5.2	-2		dBm		
Extinction Ratio	ER	3.5	5	-	dB		
Transmitter and Dispersion Penalty	TDP	-	-	3.2	dB		
Average Launch power of OFF TX	P _{off}	-	-	-30	dBm		
Optical Wavelength	λ	1260		1355	nm		
Side mode Suppression Ratio	SMSR	30			dB		
Relative Intensity Noise(OMA)	RIN ₁₂			-130	dB/Hz		
Optical Return Loss Tolerance	ORLT			12	dB		
Eye Diagram	Compatible with IEEE 802.3-2005						

PERFORMANCE SPECIFICATIONS - RECEIVER

(-5°C<T_c<+70°C; +2.97V<V_{cc}<+3.6V)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Differential Data Output Swing	V _{out}	300	-	800	mV	
Output Differential Impedance	Z _{in}	90	100	110	Ω	
Receiver sensitivity (max) in OMA	PIN-SENS(OMA)	-	-	-12.6	dBm	BER<10E -12; PRBS2^31
Receiver Sensitivity	PIN-SENS	-	-	-14.4	dBm	
Overload		0.5	-	-	dBm	
Receiver reflectance	-	-	-	-12	dB	
Optical Center Wavelength	λ _C	1270	-	1600	nm	
Los Assert		-32	-	-	dBm	
Los De-assert		-	-	-18	dBm	
Los hysteresis		0.5	-	-	dB	

REGULATORY COMPLIANCE¹

- Compliant with SFP+ MSA: SFF-8431 Rev4.1
- Compliant with SFF-8472 Rev4.4
- Compliant with IEEE802.3ae
- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- ESD to the Duplex LC Receptacle: compatible with IEC 61000-4-2 GR-1089-CORE
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

¹ The listed certifications are issued for markets in different regions. For the current status of the listed certifications in your region, please contact an authorized Starview representative.

For technical or sales support, please visit:
www.starviewint.asia

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia

MONITOR SPECIFICATION

The digital diagnostic monitoring interface also defines another 256-byte memory map in EEPROM, which makes use of the 8 bit address 1010001X (A2h). The monitoring specification of this product is described in this table.

Parameter	Range	Accuracy	Calibration
Temperature	-5 to +85°C	±3°C	Internal
Supply Voltage	2.97 to 3.63V	±3%	Internal
Bias Current	3mA to 80mA	±10%	Internal
TX Power	-8.2~0.5dBm	±3dB	Internal
RX Power	-15~0.5dBm	±3dB	Internal

NOTICE:

Inc. reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only.

Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2025 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 Williams Street, Melbourne VIC 3000, Australia