

SA-VM5508

EXTREME-NARROW BEZEL LCD VIDEO WALL



FEATURE

- Full HD 1920×1080 resolution, superb image quality
- LCD technology with Direct-lit LED backlight, uniform brightness
- Tiled bezel width of only 0.88mm (0.44mm per side)
- 178°/178° wide viewing angle, fast response speed
- 10-bit color depth, 1.07 billion colors, high color accuracy
- Designed for 24/7 operation, lifetime ≥ 60,000 hours
- Portrait and landscape display orientation
- Simple installation with 400×400mm VESA wall mount
- Low EMI; resists radiation, magnetic fields and strong electrical interference

DESCRIPTION

The Starview SA-VM5508 is a 55" extreme-narrow bezel LCD video wall built for applications that demand the very best visual performance and mission-critical reliability. Its tiled design pairs an ultra-thin 0.88mm bezel with 24/7 operation, minimal installation depth and simplified service. With a Direct-lit LED backlight and Full HD 1920×1080 resolution, it delivers uniform brightness and a wide color gamut – an excellent choice for command & control centers, security rooms, retail, broadcast, transportation, government, healthcare and corporate AV and digital signage applications.



Technical specifications

SA-VM5508

DISPLAY	Screen Size	55"
	Display Technology	LCD
	Active Display Area (W×H)	1209.6 × 680.4 mm
	Pixel Pitch	0.63 × 0.63 mm
	Panel Resolution	1920 × 1080 (16:9)
	Bezel Width	0.88mm combined bezel to bezel (0.44mm per side)
	Brightness	500 cd/m ²
	Contrast Ratio	30000:1 (Dynamic, Typ.)
	Display Colors	10-bit, 1.07 billion colors
	Viewing Angle	178° / 178°
	Response Time	≤ 6.5 ms
	Refresh Rate	60 Hz
	Backlight	Direct-lit LED
	Surface Treatment	Anti-glare (Haze 28%), Hard coating (2H)
	Lifetime	≥ 60,000 hrs
	Display Orientation	Portrait and landscape
INTERFACE	HDMI In	1 (1920×1080 backward compatible)
	USB	1
CONTROL PORT	RS232 In / Out	1 / 1
DIMENSION	Net Weight	12.5 / 12.9 kg (Typ./Max.)
	Shell Material	Metal, anti-static & anti-magnetic
	Installation	Wall mount
POWER	Voltage Input	AC 100-240 V, 50/60 Hz
	Max Power Consumption	220 W
	Standby Power Consumption	≤ 1 W
ENVIRONMENT	Working Temperature	0°C ~ 50°C
	Working Humidity	10% ~ 90% RH (Non-condensing)
ACCESSORIES	Power Cables, IR remote control	
CERTIFICATION*	CCC / CE / RoHS / FCC	

*The listed certifications are issued for markets in different regions. For the current status of the listed certifications in your region, please contact an authorized Starview representative.

For technical or sales support, please visit:

www.starviewint.asia

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. For the most up-to-date specifications, please contact an authorized Starview representative.

For assistance with confirming the Jurisdiction & Classification of Starview Asia products, please contact info@starviewint.asia

Copyright © 2026 STARVIEW ASIA. All rights reserved.
Australia Headquarters: Level 40, 140 William Street, Melbourne VIC 3000, Australia